



UL/cUL-Listed Protege Enclosures

Reference Document



The specifications and descriptions of products and services contained in this document were correct at the time of printing. Integrated Control Technology Limited reserves the right to change specifications or withdraw products without notice. No part of this document may be reproduced, photocopied, or transmitted in any form or by any means (electronic or mechanical), for any purpose, without the express written permission of Integrated Control Technology Limited. Designed and manufactured by Integrated Control Technology Limited, Protege® and the Protege® Logo are registered trademarks of Integrated Control Technology Limited. All other brand or product names are trademarks or registered trademarks of their respective holders.

Copyright © Integrated Control Technology Limited 2003-2026. All rights reserved.

Last Published: 17-Mar-26 12:06 PM

Contents

UL/cUL-Listed Protege Enclosures	4
UL Standards	4
cUL Standards	5
Technical Specifications	6
EN-DIN-11	6
EN-DIN-11-V	7
EN-DIN-12	8
EN-DIN-24	9
EN-DIN-31	10

UL/cUL-Listed Protege Enclosures

All UL/cUL installations must use an enclosure (cabinet) that is listed to the relevant UL or cUL standard. ICT offers a range of listed enclosures that are suitable for installation of Protege DIN rail products and accessories such as batteries.

This document summarizes the current UL/cUL listings for Protege enclosures, as well as their technical specifications.

Our product listings are also available on [UL Product iQ](#).

UL Standards

Standard	Listed Cabinets
UL 294 Access Control System Units	EN-DIN-11 EN-DIN-11-V EN-DIN-12 EN-DIN-24 EN-DIN-31
UL 1076 Proprietary Burglar Alarm Units and Systems	EN-DIN-11 EN-DIN-11-V EN-DIN-12 EN-DIN-24 EN-DIN-31
UL 1610 Central-Station Burglar-Alarm Units	EN-DIN-11 EN-DIN-11-V EN-DIN-12 EN-DIN-24 EN-DIN-31
UL 1635 Digital Alarm Communicator System Units	EN-DIN-11 EN-DIN-11-V EN-DIN-12 EN-DIN-24 EN-DIN-31

cUL Standards

Standard	Listed Cabinets
<p>ULC 1076 Proprietary Burglar Alarm Units and Systems</p>	<p>EN-DIN-11 EN-DIN-11-V EN-DIN-12 EN-DIN-24 EN-DIN-31</p>
<p>ULC 60839-11-1 Alarm and Electronic Security Systems - Part 11-1: Electronic Access Control Systems</p>	<p>EN-DIN-11 EN-DIN-11-V EN-DIN-12 EN-DIN-24 EN-DIN-31</p>
<p>CAN/ULC-S304 Control Units, Accessories and Receiving Equipment for Intrusion Alarm Systems</p>	<p>EN-DIN-11 EN-DIN-11-V EN-DIN-12 EN-DIN-24 EN-DIN-31</p>
<p>CAN/ULC-S319 Electronic Access Control Systems</p>	<p>EN-DIN-11 EN-DIN-11-V EN-DIN-12 EN-DIN-24 EN-DIN-31</p>
<p>CAN/ULC-S559 Equipment for Fire Signal Receiving Centres and Systems</p>	<p>EN-DIN-11 EN-DIN-11-V EN-DIN-12 EN-DIN-24 EN-DIN-31</p>

Technical Specifications

This section lists the technical specifications for each cabinet model.

EN-DIN-11

Ordering Information	
EN-DIN-11	DIN Rail Enclosure 1 x 1 Wall-Mount Metal Cabinet
Cable Entry	
Cable Knockouts	8 conduit cable knockouts 1 knockout for IEC mains voltage connector
Cable Tie Points	11 points for field wiring
Cables	Supports the Fused Panel Mount IEC C14 Socket and the Quick Connect RS-485 Daisy Chain Cable
Earthing	
Wire Looms	Bond wire looms included for earth connection to the enclosure
Accessories	
Tamper	Dedicated hardware tamper input
Lock	Cam lock
Environmental IP Rating	
IP Rating	IP50
Dimensions	
Finger Trunking Space	25mm
Dimensions (H x W x D)	400 x 280 x 102mm (15.7 x 11 x 4")
Net Weight	3.55kg (7.8lb)
Gross Weight	3.85kg (8.5lb)

EN-DIN-11-V

Ordering Information	
EN-DIN-11-V	Fire Reporting DIN Rail Enclosure 1 x 1 Wall-Mount Metal Cabinet (with viewport)
Cable Entry	
Cable Knockouts	12 conduit cable knockouts 1 knockout for IEC mains voltage connector
Cable Tie Points	11 points for field wiring
Cables	Supports the Fused Panel Mount IEC C14 Socket and the Quick Connect RS-485 Daisy Chain Cable
Earthing	
Wire Looms	Bond wire looms included for earth connection to the enclosure
Accessories	
Tamper	Dedicated hardware tamper input
Lock	Cam lock
Environmental IP Rating	
IP Rating	IP50
Dimensions	
Finger Trunking Space	25mm
Dimensions (H x W x D)	400 x 280 x 102mm (15.7 x 11 x 4")
Net Weight	3.55kg (7.8lb)
Gross Weight	3.85kg (8.5lb)

EN-DIN-12

Ordering Information	
EN-DIN-12	DIN Rail Enclosure 1 x 2 Wall-Mount Metal Cabinet
Cable Entry	
Cable Knockouts	2 conduit cable knockouts 1 knockout for IEC mains voltage connector
Cable Tie Points	12 points for field wiring
Cables	Supports the Fused Panel Mount IEC C14 Socket and the Quick Connect RS-485 Daisy Chain Cable
Earthing	
Wire Looms	Bond wire looms included for earth connection to the enclosure
Accessories	
Tamper	Dedicated hardware tamper input
Lock	Cam lock
Environmental IP Rating	
IP Rating	IP50
Dimensions	
Finger Trunking Space	25mm
Dimensions (H x W x D)	400 x 280 x 102mm (15.7 x 11 x 4")
Net Weight	3.6kg (7.9lb)
Gross Weight	3.9kg (8.6lb)

EN-DIN-24

Ordering Information	
EN-DIN-24	DIN Rail Enclosure 2 x 4 Wall-Mount Metal Cabinet
Cable Entry	
Cable Knockouts	13 conduit cable knockouts 1 knockout for IEC mains voltage connector
Cable Tie Points	26 points for field wiring
Cables	Supports the Fused Panel Mount IEC C14 Socket and the Quick Connect RS-485 Daisy Chain Cable
Earthing	
Wire Looms	Bond wire looms included for earth connection to the enclosure
Accessories	
Tamper	Dedicated hardware tamper input
Lock	Cam lock
Environmental IP Rating	
IP Rating	IP50
Dimensions	
Finger Trunking Space	25mm
Dimensions (H x W x D)	712 x 433 x 100.3mm (28 x 17 x 3.94")
Net Weight	10.5kg (23.1lb)
Gross Weight	11.0kg (24.3lb)

EN-DIN-31

Ordering Information	
EN-DIN-31	DIN Rail Enclosure 3 x 1 Wall-Mount Metal Cabinet
Cable Entry	
Cable Knockouts	7 conduit cable knockouts 1 knockout for IEC mains voltage connector
Cable Tie Points	10 points for field wiring
Cables	Supports the Fused Panel Mount IEC C14 Socket and the Quick Connect RS-485 Daisy Chain Cable
Earthing	
Wire Looms	Bond wire looms included for earth connection to the enclosure
Accessories	
Tamper	Dedicated hardware tamper input
Lock	Cam lock
Environmental IP Rating	
IP Rating	IP50
Dimensions	
Finger Trunking Space	25mm
Dimensions (H x W x D)	207 x 615 x 102mm (8.1 x 24.2 x 4.0")
Weight	4.5kg (9.9lb)

Designers & manufacturers of integrated electronic access control, security and automation products.
Designed & manufactured by Integrated Control Technology Ltd.
Copyright © Integrated Control Technology Limited 2003-2026. All rights reserved.

Disclaimer: Whilst every effort has been made to ensure accuracy in the representation of this product, neither Integrated Control Technology Ltd nor its employees shall be liable under any circumstances to any party in respect of decisions or actions they may make as a result of using this information. In accordance with the ICT policy of enhanced development, design and specifications are subject to change without notice.